

SAFETY DATA SHEET according to Regulation 1907/2006 amended by 2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**
Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

Silikat resin TYPE W1 Winter comp.B



chemius.net/KT17c

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Two component coating - component B. For professional use only.

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Supplier

SANIKOM D.O.O.
Address: Vrtna ulica 39, 4294 Križe, Slovenia
Phone: +386(0)51-354-081
Fax: 0599-50-636
E-mail: gregor.janc@sanikom.si
Point of contact for safety info: Gregor Janc

1.4. Emergency telephone number

112

+386(0)51-354-081

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Acute Tox. 4; H302 Harmful if swallowed.
Skin Irrit. 2; H315 Causes skin irritation.
Skin Sens. 1; H317 May cause an allergic skin reaction.
Eye Irrit. 2; H319 Causes serious eye irritation.
Acute Tox. 4; H332 Harmful if inhaled.
Resp. Sens. 1; H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
STOT SE 3; H335 May cause respiratory irritation.
Carc. 2; H351 Suspected of causing cancer.
STOT RE 2; H373 May cause damage to organs (Respiratory system) through prolonged or repeated exposure if inhaled.

SAFETY DATA SHEET

according to Regulation 1907/2006 amended by


2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**

Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: **Danger**

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs (Respiratory system) through prolonged or repeated exposure if inhaled.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P285 In case of inadequate ventilation wear respiratory protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P309 + P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

2.2.2. Contains:

polymeric MDI (CAS: 9016-87-9)

tris(2-chloro-1-methylethyl) phosphate (CAS: 13674-84-5, EC: 237-158-7)

2.2.3. Special provisions

Special hazards are not known or expected.

2.3. Other hazards

The substances in the mixture are not classified as persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB).

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

For mixtures see 3.2.

SAFETY DATA SHEET

according to Regulation 1907/2006 amended by

2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**

Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
polymeric MDI	9016-87-9 - -	>60	Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 Acute Tox. 4; H332 Resp. Sens. 1; H334 STOT SE 3; H335 Carc. 2; H351 STOT RE 2; H373		-
tris(2-chloro-1-methylethyl) phosphate	13674-84-5 237-158-7 -	> 10	Acute Tox. 4; H302		01-2119486772-26
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with 2,4'-diisocyanatodiphenylmethane, 2,2'-methylenebis(4-chlorophenyl) diisocyanate and α -hydro- ω -hydroxypoly[oxy(methyl-1,2-ethanediyl)]	158885-25-7 500-410-4 -	<5	Skin Irrit. 2; H315 Skin Sens. 1B; H317 Eye Irrit. 2; H319 Acute Tox. 4; H332 Resp. Sens. 1; H334 STOT SE 3; H335 Carc. 2; H351 STOT RE 2; H373		-

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

Take off all contaminated clothing immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

Following inhalation

Remove patient to fresh air - move out of dangerous area. If victim is not breathing give artificial respiration. Seek medical help immediately.

Following skin contact

Immediately remove contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If possible, rinse with polyethylene glycol 400 and plenty of water. If symptoms persist seek medical attention. Wash contaminated clothes and shoes before reuse.

SAFETY DATA SHEET

according to Regulation 1907/2006 amended by

2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**

Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. Consult a physician immediately!

Following ingestion

Do not induce vomiting! Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.

Immediately consult a doctor. Show the physician the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Coughing, sneezing, nasal discharge, labored breathing.

Headache.

Can cause sensitization.

May cause allergy or asthma symptoms or breathing difficulties if inhaled

Nausea.

Sore throat.

Skin contact

Itching, redness, pain.

May cause sensitisation by skin contact (symptoms: itching, redness, rashes).

Eye contact

Redness, tearing, pain.

Ingestion

Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area.

May cause nausea/vomiting and diarrhea.

May cause abdominal discomfort.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Symptoms of poisoning may appear several hours later. Keep under medical supervision for at least 48 hours.

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke. In the event of fire the following can be generated: carbon monoxide (CO), carbon dioxide (CO₂).

Hydrogen cyanide (HCN).

Nitrogen oxides (NO_x). Isocyanates.

5.3. Advice for firefighters

Protective actions

In case of fire or heating do not breathe fumes/vapours. Prolonged heating can cause an explosion. Cool containers at risk with water spray. If possible remove containers from endangered area.

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

SAFETY DATA SHEET

according to Regulation 1907/2006 amended by

2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**

Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

Additional information

Contaminated firefighting water must be disposed of in accordance with the regulations; do not allow to reach the sewage system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Emergency procedures

Ensure adequate ventilation. Immediately contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate personnel to safe areas, away from the direction of the wind. Prevent access to unprotected personnel. Prevent access to unauthorised personnel. Avoid contact with skin and eyes. Do not breathe vapour or mist.

6.1.2. For emergency responders

Use personal protective equipment.

6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

Stem the spill if this does not pose risks.

6.3.2. For cleaning up

Absorb with inert material (sand, flintstone (diatomite soil), universal binder, sawdust). Leave to react for at least 30 minutes. Do not absorb spillage with sawdust or other combustible material. After cleaning, wash residues with plenty of water.

6.3.3. Other information

-

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation.

Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

-

7.1.2. Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin and eyes. Do not breathe vapours/mist. Prevent concentrations of vapors above the limit values permitted at the workplace. Refer to instructions on label and regulations for safety and health at work. Use personal protective equipment. Regular cleaning of equipment, work area and clothing is recommended.

SAFETY DATA SHEET

according to Regulation 1907/2006 amended by

2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**

Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Store in accordance with local regulations. Keep in tightly closed container. Keep in cool and well ventilated area. Keep in a dry place. Keep away from incompatible products (see section 10). Keep unauthorized personnel away. Keep away from food, drink and animal feeding stuffs. Keep away from moisture and water.

7.2.2. Packaging materials

The original container of producer. Suitable material: steel. Stainless steel. Non suitable packaging material: copper. Copper alloys. Do not keep in galvanised containers.

7.2.3. Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers. Use appropriate container to avoid environmental contamination.

7.2.4. Storage class

-

7.2.5. Further information on storage conditions

-

7.3. Specific end use(s)

Recommendations

-

Industrial sector specific solutions

-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

No information.

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

8.1.3. DNEL/DMEL values

For components

Name	Type	Exposure route	Exposure frequency	Value	Remark
polymeric MDI (9016-87-9)	Worker	dermal	short term (systemic effects)	50 mg/kg bw/day	
polymeric MDI (9016-87-9)	Worker	inhalation	short term (systemic effects)	0,1 mg/m ³	
polymeric MDI (9016-87-9)	Worker	dermal	short term (local effects)	28,7 mg/cm ²	
polymeric MDI (9016-87-9)	Worker	inhalation	short term (local effects)	0,1 mg/m ³	
polymeric MDI (9016-87-9)	Worker	inhalation	long term (systemic effects)	0,05 mg/m ³	
polymeric MDI (9016-87-9)	Worker	inhalation	long term (local effects)	0,05 mg/m ³	

8.1.4. PNEC values

For components

Name	Exposure route	Value	Remark
polymeric MDI (9016-87-9)	soil	1 mg/kg	dry weight

SAFETY DATA SHEET

according to Regulation 1907/2006 amended by 2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**
Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

8.2. Exposure controls

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with eyes and skin. Do not breathe vapours/aerosols.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

8.2.2. Personal protective equipment

Eye and face protection

Safety glasses with side protection (EN 166).

Hand protection

Protective gloves (EN 374). Unsuitable material: PVC.

Appropriate materials

Material	Thickness	Penetration Time	Remark
Butyl rubber	0,7 mm	> 480 min	
Nitrile	0,4 mm	> 480 min	
chloroprene rubber	0,5 mm	> 480 min	

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

In case of insufficient ventilation wear mask with filter ABEK (EN 14387).

Thermal hazards

-

8.2.3. Environmental exposure controls

-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

-	Physical state:	liquid
-	Colour:	brown
-	Odour:	characteristic

SAFETY DATA SHEET

according to Regulation 1907/2006 amended by 2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**
Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

Important health, safety and environmental information

-	pH	No information.
-	Melting point/freezing point	No information.
-	Initial boiling point/boiling range	No information.
-	Flash point	> 200 °C (MDI)
-	Evaporation rate	No information.
-	Flammability (solid, gas)	No information.
-	Explosion limits (vol%)	No information.
-	Vapour pressure	1,0E-5 hPa at 20 °C
-	Vapour density	No information.
-	Density	Density: 1,22 – 1,26 g/cm ³ at 25 °C
-	Solubility	No information.
-	Partition coefficient	No information.
-	Auto-ignition temperature	No information.
-	Decomposition temperature	No information.
-	Viscosity	Dynamic: 310 – 370 mPas at 20 °C
-	Explosive properties	Product is not explosive.
-	Oxidising properties	No information.

9.2. Other information

-	Remarks:	
---	-----------------	--

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

Reacts with water, acids, alcohols, amines, bases and oxidants.

10.2. Chemical stability

MDI reacts quickly with water to form predominantly solid, insoluble polyureas.

10.3. Possibility of hazardous reactions

Product reacts slowly with water, releasing CO₂, which can cause overpressure in closed containers. Danger of explosion..
Acids, alcohols, amines, bases and oxidants cause fire and explosion hazard.

10.4. Conditions to avoid

High temperatures. Keep away from moisture. Avoid light.

10.5. Incompatible materials

Alcohols.
Amines.
Water.
Acids. Bases.

10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

SAFETY DATA SHEET according to Regulation 1907/2006 amended by
2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**
Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

(a) Acute toxicity

Name	Exposure route	Type	Species	Time	Value	Method	Remark
polymeric MDI (9016-87-9)	inhalation	LC ₅₀	rat	1 h	> 2,24 mg/l	OECD 403	4,4'-methylenediphenyl diisocyanate
polymeric MDI (9016-87-9)	dermal	LD ₅₀	rabbit	24 h	> 9400 mg/kg bw	OECD 402	4,4'-methylenediphenyl diisocyanate
tris(2-chloro-1-methylethyl) phosphate (13674-84-5)	oral	LD ₅₀	rat		632 mg/kg		
tris(2-chloro-1-methylethyl) phosphate (13674-84-5)	inhalation (dusts/mists)	LC ₅₀	rat	4 h	> 7 mg/l	OECD 403/OECD 433	

Additional information: Harmful if swallowed. Harmful if inhaled.

(b) Skin corrosion/irritation

Name	Species	Time	Result	Method	Remark
polymeric MDI (9016-87-9)	rabbit	14 days	Irritating.	OECD 404	4,4'-methylenediphenyl diisocyanate

Additional information: Causes skin irritation.

(c) Serious eye damage/irritation

Name	Species	Time	Result	Method	Remark
polymeric MDI (9016-87-9)	rabbit	21 days	No irritant effect.	OECD 405	4,4'-methylenediphenyl diisocyanate

Additional information: Causes serious eye irritation.

(d) Respiratory or skin sensitisation

Name	Exposure route	Species	Time	Result	Method	Remark
polymeric MDI (9016-87-9)	dermal	mouse		Sensitizing.	OECD 429	4,4'-methylenediphenyl diisocyanate
polymeric MDI (9016-87-9)	inhalation	guinea pig		Sensitizing.		4,4'-methylenediphenyl diisocyanate

Additional information: May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

Name	Exposure route	Type	Species	Time	Value	Result	Method	Remark
polymeric MDI (9016-87-9)	inhalation	NOAEC	rat	2 years	1 mg/m3			5 days per week, 6 h per day; 4,4'-methylenediphenyl diisocyanate
polymeric MDI (9016-87-9)	inhalation	LOAEC	rat	2 years	6 mg/m3			5 days per week, 6 h per day; 4,4'-methylenediphenyl diisocyanate

SAFETY DATA SHEET according to Regulation 1907/2006 amended by 2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**
Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

(g) Reproductive toxicity

Name	Reproductive toxicity type	Type	Species	Time	Value	Result	Method	Remark
polymeric MDI (9016-87-9)	Developmental toxicity	NOAEL	rat (inhalation)	10 days	4 mg/m ³			4,4'-methylenediphenyl diisocyanate
polymeric MDI (9016-87-9)	Maternal toxicity	NOAEL	rat (inhalation)	10 days	4 mg/m ³			4,4'-methylenediphenyl diisocyanate

Summary of evaluation of the CMR properties

Suspected of causing cancer.

(h) STOT-single exposure

Additional information: STOT - single exposure: May cause respiratory irritation.

(i) STOT-repeated exposure

Name	Exposure route	Type	Species	Time	Organ	Value	Result	Method	Remark
polymeric MDI (9016-87-9)	inhalation	LOAEC	rat	2 years	lungs	1 mg/m ³		OECD 453	6 h per day, 5 days per week; 4,4'-methylenediphenyl diisocyanate

Additional information: May cause damage to organs through prolonged or repeated exposure.

(j) Aspiration hazard

No information.

SECTION 12. ECOLOGICAL INFORMATION

SAFETY DATA SHEET according to Regulation 1907/2006 amended by 2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**
 Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
polymeric MDI (9016-87-9)	LC ₅₀	56,2 mg/L	96 h	fish	<i>Brachydanio rerio</i>	OECD 203	4,4'-methylenediphenyl diisocyanate
	EC ₅₀	> 1000 mg/L	24 h	crustacea	<i>Daphnia magna</i>	OECD 202	4,4'-methylenediphenyl diisocyanate
	EC ₅₀	> 1640 mg/L	72 h	algae	<i>Scenedesmus subspicatus</i>	OECD 201	4,4'-methylenediphenyl diisocyanate
	EC ₅₀	> 100 mg/L	3 h	microorganisms	Activated sludge	OECD 209	4,4'-methylenediphenyl diisocyanate
	LC ₅₀	> 1000 mg/kg soil dw	14 days	Soil macroorganisms	<i>Eisenia fetida</i>	OECD TG 207	4,4'-methylenediphenyl diisocyanate
	EC ₅₀	> 1000 mg/kg soil dw	14 days	terrestrial plants	<i>Avena sativa</i>	OECD 208	4,4'-methylenediphenyl diisocyanate
	EC ₅₀	> 1000 mg/kg soil dw	14 days	terrestrial plants	<i>Lactuca sativa</i>	OECD 208	4,4'-methylenediphenyl diisocyanate
tris(2-chloro-1-methylethyl) phosphate (13674-84-5)	LC ₅₀	56,2 mg/L	96 h	fish			
	EC ₅₀	131 mg/L	48 h	crustacea	<i>Daphnia magna</i>		

12.1.2. Chronic (long-term) toxicity

For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
polymeric MDI (9016-87-9)	NOEC	≥ 10 mg/l	21 days	crustaceans	<i>Daphnia magna</i>	OECD 211	4,4'-methylenediphenyl diisocyanate

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

For components

Substance (CAS Nr.)	Environment	Type / Method	Half Time	Evaluation	Method	Remark
polymeric MDI (9016-87-9)	Air	photodegradation	1 days	50%		4,4'-methylenediphenyl diisocyanate
polymeric MDI (9016-87-9)	water	hydrolysis	20 h	50%		25°C; 4,4'-methylenediphenyl diisocyanate

12.2.2. Biodegradation

For components

Substance (CAS Nr.)	Type	Rate	Time	Evaluation	Method	Remark
polymeric MDI (9016-87-9)	Biodegradation in water		28 days	Non-biodegradable	OECD 302 C	4,4'-methylenediphenyl diisocyanate

SAFETY DATA SHEET

according to Regulation 1907/2006 amended by 2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**
Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

For components

Substance (CAS Nr.)	species	Organism	Value	Duration	Evaluation	Method	Remark
polymeric MDI (9016-87-9)	BCF	<i>Cyprinus carpio</i>	200	28 days		OECD 305 C	4,4'-methylenediphenyl diisocyanate

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No information.

12.7. Additional information

For product

Do not allow to reach ground water, water courses or sewage system.

The product in the contact with water changes in solid, insoluble substance (polyurea). At the same time CO₂ is being released.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

Waste codes / waste designations according to LoW

08 05 01* - waste isocyanates

Packaging

Deliver completely emptied containers to approved waste disposal authorities.

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

-

SECTION 14. TRANSPORT INFORMATION

SAFETY DATA SHEET

according to Regulation 1907/2006 amended by

2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**

Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

14.1. UN number

Not applicable.

14.2. UN proper shipping name

ADR, RID, IMDG, ADN, IATA: Not dangerous according to transport regulations.

14.3. Transport hazard class(es)

Not applicable.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

NO.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Not applicable.

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

-

Abbreviations and acronyms

ATE - Acute Toxicity Estimate

ADR - Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CEN - European Committee for Standardisation

C&L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CAS# - Chemical Abstracts Service number

CMR - Carcinogen, Mutagen, or Reproductive Toxicant

CSA - Chemical Safety Assessment

CSR - Chemical Safety Report

DMEL - Derived Minimal Effect Level

DNEL - Derived No Effect Level

DPD - Dangerous Preparations Directive 1999/45/EC

DSD - Dangerous Substances Directive 67/548/EEC

DU - Downstream User

SAFETY DATA SHEET

according to Regulation 1907/2006 amended by

2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**

Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

EC - European Community
ECHA - European Chemicals Agency
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
EEC - European Economic Community
EINECS - European Inventory of Existing Commercial Substances
ELINCS - European List of notified Chemical Substances
EN - European Standard
EQS - Environmental Quality Standard
EU - European Union
Euphrac - European Phrase Catalogue
EWC - European Waste Catalogue (replaced by LoW – see below)
GES - Generic Exposure Scenario
GHS - Globally Harmonized System
IATA - International Air Transport Association
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG - International Maritime Dangerous Goods
IMSBC - International Maritime Solid Bulk Cargoes
IT - Information Technology
IUCLID - International Uniform Chemical Information Database
IUPAC - International Union for Pure Applied Chemistry
JRC - Joint Research Centre
Kow - octanol-water partition coefficient
LC₅₀ - Lethal Concentration to 50 % of a test population
LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States
MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment
(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity
(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern
UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

SAFETY DATA SHEET according to Regulation 1907/2006 amended by 2015/830/EU

Product name: **Silikat resin TYPE W1 Winter comp.B**
Creation date: **4.4.2013** · Revision: **3.8.2021** · Version: **1**

List of relevant H phrases

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer .
- H373 May cause damage to organs through prolonged or repeated exposure .



- Provided correct labelling of the product
- Compliance with the local legislation
- Provided correct classification of the product
- Provided adequate transport data

© BENS Consulting | www.bens-consulting.com

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.